



### Compact Wheel Loader LGL16F

Engine	
Model	YTR4105
Type	In-line, water cooled, direct injection
Rated power	55Kw
Rated speed	2400rpm
Main Technical Specification	
Rated load	1600kg
Operating weight	5400kg
Rated bucket capacity	0.9m <sup>3</sup>
Max.breakout force	50KN
Max.dump clearance	2700mm
Dump reach	900mm
Min. turning radius	4500mm
Lifting time of bucket	≤5s
Total cycling time	≤10s

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

website: [www.shlongji.com](http://www.shlongji.com)

[Wheel Loader](#), [Road Roller](#), [Dump Truck](#)

Tyre size	16/70-20
Transmission System	
Torque Converter	
Type	Single stage(China Shandong)
Cooling type	Pressure oil circulating
Gear box	
Type	Power shift(Shantui)
Gear shifts ( Forward/Reverse )	F2/R2
Traveling speed(Km/h)	
Forward/Reverse I	6/6
Forward/Reverse II	24/24
Dimensions	
Length(with bucket on ground)	5520mm
Width(to outside of wheels)	1960mm
Height(To the top of the cab)	2750mm
Wheel base	2200mm
Tread	1490mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

website: [www.shlongji.com](http://www.shlongji.com)

[Wheel Loader](#), [Road Roller](#), [Dump Truck](#)