



LG3251GJB Concrete Truck Mixer

Engine	
Model	Cummins C300 20
Type	Water cooled, turbocharged
Rated power	220kw
Rated speed	2200rpm
Main Technical Specification	
Chassis model	DFL5251GJB
N.V.W	14870kg
Payloading capacity	20000kg
G.V.W	35000kg
Axle loading capacity(F/R)	10000/2×16000kg
Max.traveling speed	75km
Grade ability	48%

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572

Approach angle	24°
Departure angle	30°
Ground clearance	298mm
Dimensions	
Overall size	9780×2500×3990mm
Wheel base	3800/1350mm
Tread(F/R)	2027/1820mm
Transmission System	
9JS150T-B .9 forward & 1 reverse	
Ratio	
---Forward	12.65,8.38,6.22,4.57,3.40,2.46,1.83,1.34,1.00
---Reverse	12.66
Mixer Drum	
Effective capacity	8m3
Leaning angle	12°
rotation speed	0-14rpm
Feeding speed	≥3.5m3/min
Discharging speed	≥3m3/min
Landslide speed	50-210mm
Surplus rate	≤1%
Water tank	400L
Axle And Type	
Front axle	DANA
Rear axle	HANDE
Ratio	5.73
Tyre size	12.00-20
Steering System	
ZF8098,Hydraulic steering with power assistance	
Ratio	22.2-26.2
Clutch And Brakes	
Single—plate dry coil-spring clutch, hydraulically operated with air assistance	
Service brake	Dual circuit compressed air brake
Parking brake	Spring energy operating on rear wheels
Auxiliary brake	Engine exhaust brake
Cab	
D310,four point full-floating damper, hydraulically damped adjustable driver's seat and rigid adjustable co driver's seat, heating and ventilation system ,no sleeper	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572