



LGAP60H Asphalt Paver (Hydraulic Transmission)

LGAP60H asphalt paver is used for paving road, plaza and so on, which is with compact structure and easily operated. It uses advanced double sets of hydraulic stretching screed and auto level sensing device to improve the reliability.

Engine	
Model	Cummins 4BTA3.9
Type	Water cooled, turbocharged
Rated power	93KW
Rated speed	2200rpm
Main Technical Specification	
Basic paving width	2500mm
Max. paving width	6000mm
Max. paving thickness	250mm
Min. paving thickness	10mm
Paving speed	0-10m/min
Max. theoretic productivity	400t/h
Operating weight	15000kg
Traveling Equipment	
Transmission	Full hydraulic
Under carriage	Wheel type
Type of tyres	
Front	Solid
Rear	Pneumatic
Working Equipment	
Screed plate	
Basic width	2500mm
Grade adjustment	-1-3%
Extension model	Hydraulic to 6m
Vibrating frequency	
Frequency	0-50Hz
Hoppe	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Capacity	12000kg
Discharge type	Hydraulic
Conveyor	
Independently driven	
Hydraulic control	
Electric System	
Batteries	2 sets
System voltage	24V
Dimensions	
Overall length	6070mm
Overall width	2690mm
Overall height	3020mm
Main Components	
Hydraulic pump	SAUER
Vibrating motor	SAUER
Control valve	Germany

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572