



### LGAP75H Asphalt Paver (Hydraulic Transmission)

LGAP75H asphalt paver is used for paving road, plaza and so on, which is with compact structure and easily operated. It uses advanced double sets of hydraulic stretching screed and auto level sensing device to improve the reliability.

Engine	
Model	Cummins 6BTA5.9(UK)
Type	Water cooled, turbocharged
Rated power	138KW
Rated speed	2200rpm
Main Technical Specification	
Basic paving width	2500mm
Max. paving width	7500mm
Max. paving thickness	350mm
Min. paving thickness	20mm
Paving speed	0-12m/min
Max. theoretic productivity	600t/h
Traveling Equipment	
Transmission	Full hydraulic
Under carriage	Track type
Type of Track	
-----Track length on ground	3050mm
-----width	300mm
Working Equipment	
Screed plate	
-----Basic width	2500mm
-----Grade adjustment	-1-3%
-----Extension model	Mechanical
Vibrating frequency	
-----Frequency	0-50Hz
Hopper	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Capacity	14000kg
Discharge type	Hydraulic
Conveyor	
Independently driven	
Hydraulic control	
Electric System	
Batteries	2 sets
System voltage	24V
Dimensions	
Overall length	6470mm
Overall width	2600mm
Overall height	3240mm
Main Components	
Hydraulic pump	SAUER
Vibrating motor	SAUER
Control valve	Germany

**Shanghai Longji Construction Machinery Co., Ltd.**

**Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China**

**Post Code: 201100**

**E-mail: [info@shlongji.com](mailto:info@shlongji.com)**

**Tel: +86-21-541-71571**

**Fax: +86-21-541-71572**