



Medium Wheel Loader .LGL50E

Engine	
Model	6CTA8.3
Type	Vertical, water cooled, four-stroke, direct injection
Rated power	160KW
Rated speed	2200rpm
Rated fuel consumption	220g/Kw.h
Main Technical Specification	
Rated load	5000Kg
Operating weight	16200Kg
Rated bucket capacity	3m ³
Max. breakout force	185kN
Max. dump clearance	2970mm
Dump reach	1200mm
Dump angle at any position	45°
Digging depth (with bucket bottom horizontal)	212mm
Min. turning radius	
-----Outside of bucket	6300mm
-----Outside of rear wheel	5795mm
Oscillating angle of rear axle	±11°
Lifting time of bucket	≤5.8s
Lowering time of bucket	≤3.77s
Dumping time	≤1.43s
Working Equipment	
Model of oil pump	JHP3100
System pressure	17Mpa
Model of multi-way directional valve	DF32.2C
Pilot valve	DJS2-UX/UU

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572

Axle And Tyre	
Type of main reducer	Single stage
Gear ratio of main reducer	4.625
Type of final reducer	Column straight gear planet speed reducer
Gear ratio of final reducer	4.94
total ratio	23.85
Max. tractive force	160kN
Tyre size	23.5-25
Transmission System	
Torque Converter	
Type	Single stage, double turbine, colligation(Sinoway)
Torque ratio	4
Cooling type	Pressure oil circulating
Gear box	
Type	Hydraulic gear shift(Sinoway)
Gear shifts (Forward/Reverse)	F2/R1
Traveling speed(Km/h)	
Forward/Reverse I	12.8/16
Forward II	33.4
Braking System	
Service brake	Double pipes, gas drive oil, four wheel disc type braking
Air pressure	0.68Mpa
Parking brake	Draper-type soft axle control
Steering System	
Type	Hinge joint frame, priority type, flux expanding turning system
Model of steering pump	CBGJ2080
System pressure	16MPa
Articulated steering angle	38±1°(L/R)
Dimensions	
Length(with bucket on ground)	8179mm
Width(to outside of wheels)	2946mm
Height(To the top of the cab)	3450mm
Bucket width	2975mm
Wheel base	3250mm
Tread	2240mm
Ground clearance	450mm
Service Capacities	
Fuel tank	300L
Engine crank case	22L
Converter and gear box	45L
Hydrau	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: info@shlongji.com

Tel: +86-21-541-71571

Fax: +86-21-541-71572